

Description: 2" 48mm x 914M Cold Temp Machine Tape

Product SKU: AA.21560.0

Technical Data Sheet

Formulated to be used in applications at refrigerated temperatures or at room temperature, and then stored in low temperature environments which include produce packaging, dairy facilities, meat and poultry processing plants. Performs very well in cold weather moving/storage conditions, and unheated warehouses located in cold weather climates.

Benefits of this tape include the high tack and excellent holding power, good edge tear and split resistance, and instant adherence to corrugated, paper, film, and a number of surfaces.

Backing: BOPP 1.16 / 0.029 (mils/mm)

Adhesive: Synthetic rubber and resins; transparent color

	Unit	Value
Total thickness	mils/mm	1.85 / 0.047
Adhesion to steel	oz/in. - N/100mm	27 / 29
Tensile strengt	lbs/in. - N/100mm	26 / 455
Elongation at break	%	165
Service Temperature - Min / Max	Celsius	-26 C / 38 C
Application Tempera- ture - Min / Max	Celsius	-7 C / 43 C



AA.21560.0

Phone: 866.566.2457
Email: sales@keypak.ca
Website: www.KEYPAK.ca
Fax: 866.566.2458

CONDITIONS OF USE AND CONFORMITY

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Supplier Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages.

This information is given to the best of Keypak's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.